

3600RPM 10HP 12HP 25HP Air Cooled Diesel Motor With Four **Stroke**

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: · Price: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Type: Single Cylinder, Vertical, Four-stroke, Direct

Injection, Air-cooled

73x59mm, 78x62mm, 86x72mm Borexstroke:

247ml, 296ml, 418ml Displacement: Compression Ratio: 20:01, 20:01, 19:01

3.5/3000-3.8/3600 3.68/3000-• Rated Power(kw/rpm): 4/3600 5.7/3000-6.3/3600

Rated Power(hp/rpm): 4.8/3000-5.2/3600, 5.0/3000-5.4/3600,

7.8/3000-8.6/3600

• Rated Speed(rpm): 3000/3600 • Lowest Rotation Speed At ≤1300r/min

Zero Load:

Lubricating System: Pressure Splashed Recoil Start/electric Starter . Starting System:

• Rotation Direction(face To Anticlockwise

The Output Axle):

Fuel Tunes O#/aummar\ 10#/winter\ OE#/abillages\

Product Description

GET173F GET178F GET186FA 10hp 12hp 25hp Air Cooled Diesel Engine

GET173F GET178F GET186FA Single Cylinder Air Cooled Diesel Engine

Air-cooled diesel engines are commonly used in various industrial and agricultural applications due to their simplicity, durability, and ease of maintenance. The horsepower (hp) rating of an engine refers to its power output, indicating how much work it can potentially perform. In the context you provided, you mentioned three different horsepower ratings for air-cooled diesel engines: 10hp, 12hp, and 25hp. These ratings indicate the power output of the engines. Here's a breakdown of each:

10hp Air-Cooled Diesel Engine: This engine has a power output of 10 horsepower. It is typically used in small applications such as water pumps, small generators, and lightweight machinery.

12hp Air-Cooled Diesel Engine: This engine has a slightly higher power output of 12 horsepower. It can handle slightly heavier loads compared to the 10hp engine. It is commonly used in small boats, compact tractors, and other light-duty machinery.

25hp Air-Cooled Diesel Engine: This engine has a significantly higher power output of 25 horsepower, making it suitable for more demanding applications. It can power larger generators, water pumps, and machinery requiring more torque and power.

It's worth noting that the actual performance and capabilities of an engine depend on various factors, including design, construction, fuel efficiency, and specific application requirements. When selecting an engine, it's essential to consider the intended use, load requirements, and any additional features or specifications needed for the particular application.

Model	GET188F	GET190F	GET192F	GET195F		
II vne	Single cylinder,	Single cylinder,	Single cylinder,	Single cylinder,		
	vertical, four-stroke,	vertical, four-stroke,	vertical, four-stroke,	vertical, four-stroke,		
	direct injection, air-	direct injection, air-	direct injection, air-	direct injection, air-		
	cooled	cooled	cooled	cooled		
	88.75*90mm	75*77mm	92*75mm	95*75mm		
Displaceme nt	19:01cc	19:01cc	19:01cc	19:01cc		
Compressio n Ratio	6.7/3000	7.8/3000	6.5/3000	8.1/3000		
Rated						
Power (KWipm)	7.2/3600	7.3/3600	8.2/3600	8.7/3600		
Rated						
Power (HPIIPm)	9.8/3600	10.3/3600	112/3600	11.8/3600		
Rated Speed (rpm)		3000/3600				
Lowest						
rotation		1300				
speed at						
zero loed						
Lubricating		Pressure splashad	Pressure splashad	Pressure splashad		
system						



BETge		#81, EST, ME, SM, RIMBER tings option, veltox, bur-draw, deal readon, ar-coast				
US/48 bondinte	me	75759	nree .	00.12		
H & Displacement	76.	(41)	296	10		
Edit Corpressor/tate		20.01	0041	1901		
MESSE Noted From	Millon	3.570000 3.870000	3.800000 4.5000	5.1988 6.3380		
MERS had have	Higgs	4.870000 0.270000	5.87000 8.47000	1.0300		
MERCH Sales Speed	gar	3000 / 3000				
BEDERINE Lound solder speed of very had	ritros	< 100				
Will fast submaring system		EXTMX Propus system				
Bild Sunguen		EGRESTEER Focus Service visitor				
Minimatry (#DYM/6/M) Relation direction(box to the output ank)		BRTT Attocowine				
MARY Factors		0 + 1 2 3 1 - 10 + 1 0 3 1 - 10 + 1 2 2 1 2 2 1 2 2 2 4 1 suprem 7 - 10 + 1 suprem 1 - 10 + 1 suprem 1 done				
MARKE Fuel lark capacity	L.	2.0	2.0	88		
株式後年平式支持者 Fusionsumptoni MERCHARIO GORDGER NYME)		290-27000 290-27000	E%-900 90.0000	(% 1000 (#1.5000)		
REMIND Life of type		(0 gast or SAC 16N-91, 15M-91				
現中教育者 Lide-of rispecty	L.	1/5	1.1	1.00		
G In To A Sign Starting motor reportly	11,100	17/18/8				
mamaries Danging presente capacity	V. a.	127 8.34				
STATE Sales specify	V. m	50Y 20W	GV 334s	12V 30An		
MERT Consideration (Lot Roll)	me	430'Y00'Y00	eoneonina	30740746		
## to want	No.		20	- 4		



GET Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@gg.com



@ dieselenginepumps.com