Portable Open Type Diesel Generator Set 220V 50hz Low Noise

Basic Information

- Place of Origin:
- Brand Name:

GET

- Certification:
- Price:
- Delivery Time: 15-20 workd

China

GET

ISO CE

- Payment Terms:
- Negotiable 15-20 workdays LC, T/T, PayPal, Western Union, Smallamount payment, Money Gram



Product Specification

 Rated Frequency: 	50hz 60hz	
• Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8	
• Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4	
 Rated Voltage (V): 	220V Or As Request	
• Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9	
Rated Rotation Speed (r/min):	3000 3600	
Phase No.:	Single Phase	
 Power Factor: 	1	
 Insulation Grade: 	F	
Pole Number:	2	
Excitation Mode:	Self-excitation & Constant Voltage (AVR)	
• Panel Type:	General Panel	

GET9500E Portable Open Type Diesel Generator Set Outdoor And Indoor

Description:

An open type diesel generator refers to a generator set that is designed without an enclosure or housing surrounding the engine and alternator. It is also commonly known as an open frame or open skid generator.

Hated Outpul(kw): 1.5 2.0/ 2.5 2.6/ 4.5 3.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8 Rated Voltage (V): 220V Or As Request Rated Notation 3000 3600 Speed (r/min): 3000 3600 Power Factor: 1 Pole Number: 2 Panel Type: General Panel Connection Pole: Without Overall 690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Struck (mm): 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor CD Grade Or SAE10W-30, 15W-40 Starting Motor CD 2/2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 2.5.7/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 2.5.7/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4		
Rated Rotation 3000 3600 Speed (r/min): 3000 3600 Power Factor: 1 Pole Number: 2 Panel Type: General Panel Connection Pole: Without Overall 690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting 66 83 110 115 120 125 Weight (kg): 51 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Stroke (mm): 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000- 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Cill Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor C29 acity: Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: Soln 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5 / 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rat	Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8
Speed (r/min): 3000 3600 Power Factor: 1 Pole Number: 2 Panel Type: General Panel Connection Pole: Without Overall 690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting 66 83 110 115 120 125 Structure Type: Open Type Cylinder No -bore X 1.73x55/ 1.78x62/ 1.86x72/ 1.88x75/ 1.92x75/ 1.95x75 Stroke (mm): 1.73x55/ 1.78x62/ 1.86x72/ 1.88x75/ 1.92x75/ 1.95x75 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase		220V Or As Request
Power Factor: 1 Pole Number: 2 Panel Type: General Panel Connection Pole: Without Overall 690x480x560/ 690x480x560/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Stroke (mm): 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 3.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle:		3000 3600
Pole Number: 2 Panel Type: General Panel Connection Pole: Without Overall 690x480x560/690x480x560/730x495x630/730x495x630/ Dmension(mm): 730x495x630/730x495x655 Working Assorting 66 83 110 115 120 125 Weight (kg): 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Stroke (mm): 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F <td></td> <td></td>		
Panel Type: General Panel Connection Pole: Without Overall 690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Struck (mm): 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor C2V 0.9KW/ 12V 1.2KW Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 20Ah / 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR)		
Connection Pole: Without Overall 690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Stroke (mm): 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 30Ah Fuel Tank Capacity 12.5.5/5.5.5.7/ 6.6 6.8/ 6.9 7.4 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output:		
Overall 690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/ Dmension(mm): 730x495x630/ 730x495x655 Working Assorting Weight (kg): 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X Stroke (mm): 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Rated Power: 7.2/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000- 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4		
Dmension(mm): 730x495x630/730x495x655 Working Assorting Weight (kg): 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/1-78x62/1-86x72/1-88x75/1-92x75/1-95x75 Stroke (mm): 1-73x55/1-78x62/1-86x72/1-88x75/1-92x75/1-95x75 Rated Power: 2.5/3000-2.8/3600.3.68/3000-4/3600.5.7/3000-6.3/3600.6.5/3000- 7.2/3600.7.6/3000-8.2/3600.8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/12V 1.2KW Battery Capacity: 12V 0.9KW/12V 30Ah Fuel Tank Capacity 13.5 (L): 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 <td></td> <td></td>		
Working Assorting Weight (kg): 66 83 110 115 120 125 Structure Type: Open Type Cylinder Nobore X Stroke (mm): 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000- 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lubrication System: Pressure Splashed Lubr Oil Brand: CD Grade Or SAE 10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 0.9KW/ 12V 30Ah Fuel Tank Capacity 13.5 (L): Rated Frequency: Sohz 60hz 5.2.7 2.0 / 5.2 5.5 / 5.5 5.7 / 6.6 6.8 / 6.9 7.4 Rated Currency (A): 7.8 8.7 / 11.3 12.7 / 20.5 22.7 / 22.7 23.6 / 27.2 28.2 / 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Ve		
Weight (kg): 06 05 110 115 120 125 Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Stroke (mm): 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Inject		730x495x630/ 730x495x655
Weight (kg): Description Structure Type: Open Type Cylinder Nobore X 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Stroke (mm): 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418		66 83 110 115 120 125
Cylinder Nobore X Stroke (mm): 1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000- 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Capacity: 12V 0.9KW/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled <tr< td=""><td></td><td></td></tr<>		
Stroke (mm): 1-73355/1-76802/1-6687/2/1-6887/5/1-9287/5/1-9587/5 Rated Power: 2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Capacity: 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: <td< td=""><td></td><td>Open Type</td></td<>		Open Type
Hated Power: 7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 2001, 19:01 Fuel Type: Ø#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumpt		1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600 Lubrication System: Pressure Splashed Lube Oil Brand: CD Grade Or SAE10W-30, 15W-40 Starting Motor 12V 0.9KW/ 12V 1.2KW Battery Capacity: 12V 20Ah/ 12V 30Ah Fuel Tank Capacity 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 200	Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-
Lube Oil Brand:CD Grade Or SAE10W-30, 15W-40Starting Motor Capacity:12V 0.9KW/ 12V 1.2KWBattery Capacity:12V 20Ah/ 12V 30AhFuel Tank Capacity13.5Rated Frequency:50hz 60hzMax Output (kw):2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4Rated Currency (A):7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9Phase No.:Single PhaseInsulation Grade:FExcitation Mode:Self-excitation & Constant Voltage (AVR)Receptacle:Two ReceptaclesDC 12V Output:Connection Pole OutputDry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator Capacity:12V 8.3AFuel Consumption1202		
Starting Motor Capacity:12V 0.9KW/ 12V 1.2KWBattery Capacity:12V 20Ah/ 12V 30AhFuel Tank Capacity (L):13.5Rated Frequency:50hz 60hzMax Output (kw):2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4Rated Currency (A):7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9Phase No.:Single PhaseInsulation Grade:FExcitation Mode:Self-excitation & Constant Voltage (AVR)Receptacle:Two ReceptaclesDC 12V Output:Connection Pole OutputDry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator Capacity:12V 8.3AFuel Consumption200	Lubrication System:	
Capacity:12V 0.9KW/12V 1.2KWBattery Capacity:12V 20Ah/12V 30AhFuel Tank Capacity:13.5Rated Frequency:50hz 60hzMax Output (kw):2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4Rated Currency (A):7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9Phase No.:Single PhaseInsulation Grade:FExcitation Mode:Self-excitation & Constant Voltage (AVR)Receptacle:Two ReceptaclesDC 12V Output:Connection Pole OutputDry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator12V 8.3AFuel Consumption200		CD Grade Or SAE10W-30, 15W-40
Capacity:12V 20Ah/ 12V 30AhBattery Capacity:12V 20Ah/ 12V 30AhFuel Tank Capacity13.5Rated Frequency:50hz 60hzMax Output (kw):2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4Rated Currency (A):7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9Phase No.:Single PhaseInsulation Grade:FExcitation Mode:Self-excitation & Constant Voltage (AVR)Receptacle:Two ReceptaclesDC 12V Output:Connection Pole OutputDry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator12V 8.3AFuel Consumption200		12V 0 9KW/ 12V 1 2KW
Fuel Tank Capacity (L): 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 200		
(L): 13.5 Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 200		12V 20Ah/ 12V 30Ah
(L): For an analysis Rated Frequency: 50hz 60hz Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 200		13.5
Max Output (kw): 2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4 Rated Currency (A): 7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9 Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 200	· · ·	
Rated Currency (A):7.88.7/11.312.7/20.522.7/22.723.6/27.228.2/28.630.9Phase No.:Single PhaseInsulation Grade:FExcitation Mode:Self-excitation & Constant Voltage (AVR)Receptacle:Two ReceptaclesDC 12V Output:Connection Pole OutputDry Weight (kg):5370100105110115Noise Level (7m):77DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247296418456498531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.751.11.65Charging Generator Capacity:12V8.3AFuel Consumption200		
Phase No.: Single Phase Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 200		
Insulation Grade: F Excitation Mode: Self-excitation & Constant Voltage (AVR) Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator 12V 8.3A Fuel Consumption 2000	Rated Currency (A):	
Excitation Mode:Self-excitation & Constant Voltage (AVR)Receptacle:Two ReceptaclesDC 12V Output:Connection Pole OutputDry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator Capacity:12V 8.3AFuel Consumption2000	Phase No.:	Single Phase
Receptacle: Two Receptacles DC 12V Output: Connection Pole Output Dry Weight (kg): 53 70 100 105 110 115 Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption 2000	Insulation Grade:	F
DC 12V Output:Connection Pole OutputDry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator Capacity:12V 8.3AFuel Consumption2000	Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Dry Weight (kg):53 70 100 105 110 115Noise Level (7m):77 DBEngine Type:Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooledDisplacement(ml):247 296 418 456 498 531Compression Ratio:20:01, 19:01Fuel Type:0#(summer)-10#(winter)-35#(chillness) DieselLube Capacity (L):0.75 1.1 1.65Charging Generator Capacity:12V 8.3A	Receptacle:	Two Receptacles
Noise Level (7m): 77 DB Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A	DC 12V Output:	Connection Pole Output
Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption 2000	Dry Weight (kg):	53 70 100 105 110 115
Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption 2000	Noise Level (7m):	77 DB
Displacement(ml): 247 296 418 456 498 531 Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption 2000	Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Compression Ratio: 20:01, 19:01 Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption -000		
Fuel Type: 0#(summer)-10#(winter)-35#(chillness) Diesel Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption	Compression Ratio:	20:01, 19:01
Lube Capacity (L): 0.75 1.1 1.65 Charging Generator Capacity: 12V 8.3A Fuel Consumption		0#(summer)-10#(winter)-35#(chillness) Diesel
Charging Generator Capacity: Fuel Consumption	1 21	
	Charging Generator	12V 8.3A
	Fuel Consumption	≤280

Details:

1. Engine: The open type diesel generator is equipped with a diesel engine as its primary power source. Diesel engines are known for their durability, fuel efficiency, and reliability. They are specifically designed for continuous or standby power generation and can provide a stable power supply for various applications.

2. Alternator: The generator set includes an alternator, which converts mechanical energy from the diesel engine into electrical energy. The alternator is responsible for generating the electric power output and maintaining a stable voltage and frequency.

3. Skid-Mounted Frame: The open type diesel generator is mounted on a sturdy skid base or frame. The skid base provides stability and allows for easy transportation and installation. It typically includes lifting points or forklift slots for convenient handling and positioning.

4. Cooling System: To maintain optimal operating temperature, the open type diesel generator incorporates a cooling system. It may include features such as a radiator, cooling fan, and coolant circulation system. The cooling system prevents overheating of the engine and ensures efficient and reliable performance.

5. Control Panel: An open type diesel generator is equipped with a control panel that allows operators to monitor and control the generator's operation. The control panel typically includes instruments and controls for monitoring voltage, frequency, current, and other essential parameters. It may also provide features such as engine start/stop controls, circuit breakers, and safety shutdowns.

6. Exhaust System: The generator set includes an exhaust system to safely discharge the combustion gases produced by the diesel engine. The exhaust system typically includes a muffler or silencer to reduce noise levels and may include piping and ventilation components for proper exhaust disposal.

7. Fuel System: An open type diesel generator incorporates a fuel system for supplying diesel fuel to the engine. It typically includes a fuel tank, fuel filters, fuel lines, and a fuel pump. The fuel system ensures a consistent and reliable fuel supply to the engine for uninterrupted operation.



