



Red Diesel Welding Generator 186FA 192F Diesel Engine Welder Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Power (kw): 2.5
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 8.7 9.5A
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- No Load Welding Voltage: 65-70V
- Insulation Grade: F
- Pole Number: 2
- Engine Mode: GET186FA GET192F
- Displacement(ml): 418 456
- Engine Type: Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
- Bore X Stroke (mm): 4.00x70/4.00x75

for more products please visit us on diesenginepumps.com

GET6500EAW Diesel Generator And Welder Diesel Operated Welding Machine

Maintenance and Repair: Diesel welder generators are commonly used for maintenance and repair work in various industries. They enable technicians and welders to carry out welding tasks at different locations, such as equipment repairs, pipeline welding, and maintenance of agricultural machinery.

The versatility, portability, and self-contained nature of portable diesel welder generators make them indispensable in various industries and settings where a combination of power and welding capabilities is needed on the go.

Rated Power (kw):	2 5
Rated Current (A):	8.7 9.5A
Phase No.:	Single Phase
No Load Welding Voltage:	65-70V
Pole Number:	2
Displacement(ml):	418 456
Bore X Stroke (mm):	1-86x72/ 1-92x75
Rated Power:	5.7 6.3/ 7.2 8.2
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Fuel Tank Capacity (L):	13.5
Rated Welding Current:	180A 220A
Welding Load Continuous Ratio:	60%
Electrode Diameter:	1.6-3.2mm 1.6-5.0mm
Rectifying Mode:	Diode
Overall Dimension:	720x492x655mm
Dry Weight:	112kg 116kg
Rated Frequency:	50hz 60hz
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Insulation Grade:	F
Engine Mode:	GET186FA GET192F
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Compression Ratio:	19:01
Lubrication System:	Pressure Splashed
Lube Capacity (L):	1.65
Fuel Consumption (g/kw*h):	≤280
Continuous Running Time:	8h
Welding Voltage:	25-30V
Welding Current Adjustment Range:	50-180A/ 50-200A
Excitation Mode:	Separate-excitation+AVR Voltage Regulation AVR
Connection Mode:	Drive Bearing, Rigid Connection
Structure Type:	Open Type

电焊发电机系列 Diesel Welding Generator Series



參數表 Specifications

[illegible]



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA