



## GET Diesel Engine Pumps 4 Inch 6 Inch Diesel Water Pump

Our Product Introduction

### Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



### Product Specification

- Type: Diesel Water Pump
- Suction/discharger Port Diameter Mm(inch): 50(2'). 80(3'). 100(4'). 150(6')
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on [dieselenginepumps.com](http://dieselenginepumps.com)

## Product Description

### GET Diesel Engine Pumps Diesel Engine Fire Pump

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	

Industrial diesel engine pumps are widely used in various applications, including irrigation, construction, mining, oil and gas, and wastewater management. These pumps are designed to provide high-performance pumping capabilities in demanding industrial environments. Here are some key features and characteristics of industrial diesel engine pumps:

**Self-Priming Capability:** Some industrial diesel engine pumps are equipped with self-priming capabilities. This means they can automatically prime themselves and create suction to draw the fluid into the pump, eliminating the need for manual priming or the use of external priming equipment.

**Fuel Efficiency:** Industrial diesel engine pumps are designed to be fuel-efficient, optimizing the consumption of diesel fuel during operation. This reduces operating costs, especially in applications where the pump runs for extended periods.

**Control and Monitoring Systems:** Many modern industrial diesel engine pumps come with advanced control and monitoring systems. These systems allow for remote operation, monitoring of pump performance, and integration with other control systems in the industrial process.

**Safety Features:** Industrial diesel engine pumps often incorporate safety features to protect the pump system and operators. These may include overload protection, low oil pressure shutdown, temperature monitoring, and emergency stop functions.

**Maintenance and Serviceability:** Industrial diesel engine pumps are designed for ease of maintenance and serviceability. They typically have accessible components for inspection, routine maintenance, and repairs. Manufacturers may also provide maintenance schedules and guidelines to ensure optimal performance and longevity of the pump.



参数表 Specifications

	10T/100L	15T/150L	20T/200L	25T/250L	30T/300L
产品系列 Product Series	10T/100L	15T/150L	20T/200L	25T/250L	30T/300L
额定流量 Rated Flow (m³/h)	10	15	20	25	30
最大流量 Max. Flow (m³/h)	12	18	24	30	36
额定扬程 Rated Head (m)	10	15	20	25	30
最大扬程 Max. Head (m)	12	18	24	30	36
额定功率 Rated Power (kW)	10	15	20	25	30
最大功率 Max. Power (kW)	12	18	24	30	36
额定转速 Rated Speed (rpm)	1500	1500	1500	1500	1500
最大转速 Max. Speed (rpm)	1800	1800	1800	1800	1800
额定电压 Rated Voltage (V)	220	220	220	220	220
额定电流 Rated Current (A)	10	15	20	25	30
额定功率因数 Rated Power Factor	0.85	0.85	0.85	0.85	0.85
额定效率 Rated Efficiency (%)	85	85	85	85	85
额定寿命 Rated Life (h)	1000	1000	1000	1000	1000
额定重量 Rated Weight (kg)	100	150	200	250	300
额定尺寸 Rated Size (mm)	1000x1000x1000	1500x1500x1500	2000x2000x2000	2500x2500x2500	3000x3000x3000
额定噪音 Rated Noise (dB)	85	85	85	85	85
额定振动 Rated Vibration (mm/s²)	10	10	10	10	10
额定防护等级 Rated Protection Class	IP55	IP55	IP55	IP55	IP55
额定环境温度 Rated Ambient Temp (°C)	-20	-20	-20	-20	-20
额定相对湿度 Rated Relative Humidity (%)	95	95	95	95	95
额定海拔 Rated Altitude (m)	1000	1000	1000	1000	1000
额定安装方式 Rated Installation	Horizontal	Horizontal	Horizontal	Horizontal	Horizontal
额定使用条件 Rated Conditions	Normal	Normal	Normal	Normal	Normal
额定维护周期 Rated Maintenance Cycle	1000h	1000h	1000h	1000h	1000h
额定保修期 Rated Warranty Period	12 months	12 months	12 months	12 months	12 months
额定售后服务 Rated After-sales Service	24h	24h	24h	24h	24h

**GET Wuxi Guangertai Power Machinery Co.,Ltd**

☎ 13813650506    ✉ 2415819289@qq.com    🌐 [dieselenginepumps.com](http://dieselenginepumps.com)

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA